

# LODESTONE PACIFIC




Phone: (800) 694-8089  
 www.lodestonepacific.com  
 E-mail: sales@lodestonepacific.com

## KM SERIES

Material: Vydyn 909 (Black)  
 UL Rating: UL 94-V0, Class F  
 2 Terminals: Self Terminating  
 Solderability: Per MIL-STD-202 Method 208  
 Packaging: Bulk in Polybags

Application: "Klip" mounts are designed as a "self-leaded" inductor mount for wound toroids from .030 to 1.10 inches in diameter. The molded "Klip" holds the toroid leads for circuit board termination.



PART NO.	LENGTH	WIDTH	A	B	HT.	T	X	KLIP WIRE SIZE	TOROID DIA.	PACKING TRAY
KM44-01	.580	.340	.480	.240	.280	.110	.220	24-23 AWG	.450	TY74x77-A
KM44-02	[14.73]	[8.63]	[12.19]	[6.09]	[7.11]	[2.79]	[5.58]	22-21 AWG		
KM50-01	.650	.450	.550	.350	.300	.110	.300	24-21 AWG	.550	TY74x77-A
KM50-02	[16.51]	[11.43]	[13.97]	[8.89]	[7.62]	[2.79]	[7.62]	20-18 AWG		
KM68-01	.830	.450	.730	.350	.370	.110	.300	24-21 AWG	.725	TY65x100-A
KM68-02	[21.08]	[11.43]	[18.54]	[8.89]	[9.39]	[2.79]	[7.62]	20-18 AWG		
KM80-01	.950	.600	.850	.500	.420	.110	.450	22-19 AWG	.850	TY122x140-A
KM80-02	[24.13]	[15.24]	[21.59]	[12.7]	[10.66]	[2.79]	[11.43]	18-17 AWG		
KM106-01	1.250	.700	1.150	.600	.580	.130	.500	22-19 AWG	1.150	TY122x140-A
KM106-02	[31.75]	[17.78]	[29.21]	[15.24]	[14.73]	[3.30]	[12.7]	18-17 AWG		

[Request a Sample](#)

[View Inventory](#)

[Request a Quote](#)

[Toroid Mount Selector](#)

[REACH Database](#)

[Coil Winder Database](#)